


STANDARD DEPARTURE CHART - INSTRUMENT (SID) - ICAO

DIST IN NM
BEARINGS ARE MAGNETIC
ALTITUDES AND ELEV IN FEET

DOHA RADAR 121.10
DOHA APP 119.725 / 120.60
TWR 118.90 / 119.025

DOHA/Doha Intl. (OTBD)
RNP RWY 15
SALWA 1S



STANDARD DEPARTURE
CHART - INSTRUMENT
(SID) - ICAO

DOHA/Doha Intl.(OTBD)
RNP RWY 15
SALWA 1S

TABULAR DESCRIPTION

RNP SID SALWA 1S											
Serial Num	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation(°)	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt)	VPA(°)/TCH(ft)	Navigation Specification
1	CF	ITОВI	-	156 (158.2)	2.3	-	-	-	-250	-	RNP 1
2	TF	OBVER	-	171 (173.2)	2.3	7.7	R	+4000	-250	-	RNP 1
3	TF	SODER	-	261 (263.2)	2.3	5.0	-	-	-	-	RNP 1
4	TF	BOXED	-	284 (286.0)	2.3	5.0	-	+5000	-	-	RNP 1
5	TF	DEBKO	-	284 (286.0)	2.3	5.0	-	+6000	-	-	RNP 1
6	TF	DEKTO	-	284 (285.9)	2.3	5.0	-	@7000	-	-	RNP 1
7	TF	SALWA	-	284 (285.9)	2.3	43.5	-	-	-	-	RNP 1

WAYPOINT LIST

RNP SID SALWA 1S	
Waypoint Identifier	Coordinates
ITОВI	250758.29N 0513717.60E
OBVER	250016.73N 0513818.23E
SODER	245940.88N 0513250.24E
BOXED	250103.72N 0512732.63E
DEBKO	250226.38N 0512214.90E
DEKTO	250348.84N 0511657.05E
SALWA	251538.00N 0503048.00E