

STANDARD DEPARTURE
CHART - INSTRUMENT
(SID) - ICAO

DOHA/Hamad Intl.(OTHH)
RNP RWY 34L
PATOM 2W

TABULAR DESCRIPTION

RNP SID PATOM 2W											
Serial Num	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation(°)	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt)	VPA(°)/TCH(ft)	Navigation Specification
1	CF	OVASA	-	335 (338.1)	-2.6	8.0	-	+2500	-	-	RNP 1
2	TF	PARES	-	335 (338.1)	-2.6	4.5	-	@4000	-	-	RNP 1
3	TF	KOBEN	-	014 (016.5)	-2.6	10.7	-	-	-	-	RNP 1
4	TF	ALNAK	-	359 (002.1)	-2.6	11.5	-	-	-	-	RNP 1
5	TF	PATOM	-	296 (298.2)	-2.6	15.8	-	+FL160	-	-	RNP 1
Remarks		PATOM +FL160 by ATC only									

WAYPOINT LIST

RNP SID PATOM 2W	
Waypoint Identifier	Coordinates
OVASA	252455.76N 0513204.45E
PARES	252906.58N 0513013.12E
KOBEN	253921.98N 0513334.39E
ALNAK	255053.49N 0513401.89E
PATOM	255821.41N 0511836.36E