



DOHA/Hamad Intl.(OTHH)
RNP RWY 34R (LNAV/VNAV only)
ACFT A,B,C,D

AD ELEV 13
HEIGHTS RELATED TO AD ELEV

INSTRUMENT
APPROACH
CHART-ICAO

TABULAR DESCRIPTION

RNP RWY 34R DANIK											
Serial Num	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt)	VPA/ TCH	Navigation Specification
1	IF	DANIK	-		2.3	-		+5000	-220		RNP 1.0
2	TF	LAGMA	-	066 (068.1)	2.3	6.1	L	+3000	-180		RNP 1.0

RNP RWY 34R EMUNA											
Serial Num	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt)	VPA/ TCH	Navigation Specification
1	IF	EMUNA	-		2.3	-		+5000	-220		RNP 1.0
2	TF	LAGMA	-	342 (344.4)	2.3	5		+3000	-180		RNP 1.0

RNP RWY 34R MUXED											
Serial Num	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt)	VPA/ TCH	Navigation Specification
1	IF	MUXED	-		2.3			+5000	-220		RNP 1.0
2	TF	LAGMA	-	246 (248.3)	2.3	5	R	+3000	-180		RNP 1.0

RNP RWY 34R FINAL											
Serial Num	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt)	VPA/ TCH	Navigation Specification
1	IF	LAGMA	-		2.3	-		+3000	-180		RNP 1.0
2	TF	HH901	-	336 (338.2)	2.3	5		+3000	-180		RNP 0.3
3	TF	RW34R	Y	336 (338.2)	2.3	9.2		-	-180	-3.0/50	RNP 0.3
4	CF	HH902	Y	336 (338.2)	2.3	-		-	-230		RNP 1.0
5	TF	GOMBO	-	031 (033.5)	2.3	13.9	R	-	-230		RNP 1.0
6	TF	GENOT	-	146 (148.3)	2.3	11.1		@4000	-230		RNP 1.0
7	HM	GENOT	Y	066 (068.3)	2.3	4.3	R	@4000	-230		RNP 1.0

WAYPOINT LIST

RNP RWY 34R	
Waypoint Identifier	Coordinates
DANIK	245948.49N 0513712.89E
EMUNA	245712.86N 0514455.31E
GENOT	252018.11N 0515114.66E
GOMBO	252944.22N 0514450.16E
HH901	250644.17N 0514123.09E
HH902	251807.32N 0513622.55E
LAGMA	250204.62N 0514325.78E
MUXED	250356.10N 0514832.78E
RW34R	251519.65N 0513736.41E